


**MIGHTY LUBE®**



Systematic Lubrication, Inc.

**MIGHTY LUBE**  
Systematic Lubrication, Inc.

## TECHNICAL DATA SHEET

### MIGHTY LUBE TYPE GL LUBRICANT The New "Green" Lubricant

Mighty Lube Type GL lubricant is a specially designed "green" thin film, anti-wear penetrating lubricant. Type GL uses a naturally occurring biodegradable, environmentally friendly and non-toxic penetrating solvent / cleaner, with an attractive citrus aroma.

Specially formulated for the coating industry, Type GL uses synthetic ester based fluids that provide a semi-wet, thin film lubricant which will work at temperatures up to 575° F. Type GL lubricant will break down other inferior lubricants or carbons and help clean the conveyor.

Mighty Lube Type GL is a green lubricant specially designed to lubricate and leave no residuals or carbons. Mighty Lube Type GL lubricant functions as a penetrating lubricant. The solvent acts as a penetrator carrying the base fluids to the moving parts or wear points. The base fluids provide excellent film strength and corrosion protection providing trouble free lubrication. Precise controlled ejections by Mighty Lube Systematic Lubrication Equipment controls the amount of lubricant used, thus eliminating under and over lubrication.

Mighty Lube Systematic Lubrication lubricants and equipment are the result of years of development. Together they produce a highly technical system that provides maximum protection against wear, corrosion and insures trouble free operations without waste and downtime.

#### TYPICAL SPECIFICATIONS

Viscosity SUS @100°F.	40
Pour Point °F.	-65
Flash Point °F.	125
Color	Light Amber
Lubricant Base	Ester Synthetic
Rust Preventive Properties (ASTM D665A)	No Corrosion