

MIGHTY LUBE



Systematic Lubrication, Inc.

MIGHTY LUBE SYSTEMATIC LUBRICATION

TECHNICAL DATA SHEET

TYPE ML-L LUBRICANT

Mighty Lube Type ML-L Lubricant is a clear, heavy duty anti-wear lubricant which protects against wear and corrosion over temperature ranges of -65 degrees F to 425 degrees F.

Mighty Lube Type ML-L Lubricant is a result of specialty chemicals being formulated to exceed all the characteristics of an excellent lubricant. Type ML-L Lubricant consists of a mineral spirit solvent which acts as a cleaner, penetrator and carrier, providing a pathway for the other components to work their way into the wear points. Synthetic fluids act as the base for this and provide a semi-wet, thin film lubricant. Other components include surfactant for moisture displacement and rust inhibitors for corrosion protection.

Mighty Lube Type ML-L Lubricant functions much as a penetrating lubricant. The mineral spirits are the penetrator carrying the synthetic fluids base to the moving parts of wear points. The mineral spirits solvent eventually evaporates, leaving the base of synthetic fluids behind. The base provides a semi-wet, thin film of lubricant of excellent film strength providing trouble-free lubrication. Precise controlled ejections by Mighty Lube Systematic Lubrication Equipment controls the amount of lubricant used, thus eliminating under and over lubrication.

Mighty Lube Systematic Lubrication Lubricants and Equipment are the result of years of development. Together they produce a highly technical system that provides maximum protection against wear, corrosion and insures trouble free operations without waste and down time.

TYPICAL SPECIFICATIONS

Viscosity SUS @100°F.	35
Pour Point °F.	-65
Flash Point °F.	125
Color	Light Amber
Viscosity Index	135
Lubricant Base	Ester Synthetic
Rust Preventive Properties (ASTM D665A)	No Corrosion

Mfg. by Mighty Lube Systematic Lubrication, Inc., Fremont, MI 49412

231-924-6160

www.mightylube.com