

**MIGHTY LUBE®**



Systematic Lubrication, Inc.

## **MIGHTY LUBE SYSTEMATIC LUBRICATION**

### **TECHNICAL DATA SHEET**

### **TYPE SYN LUBRICANT**

Mighty Lube Type SYN Lubricant is a heavy duty, anti-wear lubricants, which have been formulated to withstand the most extreme industrial conveyor applications.

The use of the Mighty Lube Systematic Lubrication will result in a conveyor system that is protected against wear and corrosion over temperature ranges of -55°F to 550°F.

Mighty Lube Type SYN Lubricant is a result of specialty chemicals being formulated to exceed all the characteristics of an excellent lubricant. Type SYN Lubricant consist of a base fluid that acts as a cleaner, penetrator and carrier providing a pathway for the other components to work their way into the wear points.

Mighty Lube Type SYN Lubricant functions much as a penetrating lubricant, carrying to moving parts the synthetic fluids. This provides a lubricant of excellent film strength providing trouble free lubrication. Timed ejection by lubrication equipment controls the amount of lubricant used, thus eliminating under and over lubrication.

Mighty Lube Type SYN Lubricant and Mighty Lube Lubrication Equipment are a result of years of development to produce a highly technical system that provides maximum protection against wear, corrosion, and to insure trouble free operation without waste and equipment down time.

#### **TYPICAL SPECIFICATIONS**

Viscosity SUS @100°F.	70
Pour Point °F.	-45
Flash Point °F.	430
Color	Amber semi-clear
Viscosity Index	150
Four Ball Wear Scar, mm, ASTM D-2266	0.38

Mfg. by Mighty Lube Systematic Lubrication, Inc., Fremont, MI 49412  
231-924-6160